

DATA SHEET

Titan XQ 400 AC puls DW


090-005607-00001



- MIG/MAG inverter welding machine, pulse, with separate wire feeder
- acArc puls XQ – ideal for aluminium welding with thin sheets
- Thanks to the acArc puls XQ, you can create clean weld seams on even the thinnest metal sheets without any burn marks
- Perfect MIG/MAG weld seams even with long welding leads
- Synergic control with one-knob operation
- No controls on the welding machine.
- The machine is controlled exclusively via the selected wire feeder.



No need to purchase additional characteristics – all characteristics for this machine type are included in the scope of delivery ex works

- With all AC and established DC MIG/MAG characteristics: acArc puls XQ, rootArc® XQ/rootArc® puls XQ, coldArc® XQ/coldArc® puls XQ, forceArc® XQ/forceArc® puls XQ, wiredArc XQ/wiredArc puls XQ, pulse/superPuls and Positionweld
 - To find out more about our high-tech MIG/MAG arcs, please click on XQ-Process 
 - Synergic characteristics for flux-cored wires
 - Non Synergic operation for manual setting of welding parameters
 - Also suitable for MMA welding, TIG welding and gouging
 - Individually configurable programs for JOBS (welding tasks)
 - Adjustable start and end-crater functions
 - Infinitely adjustable arc dynamics (choke effect)
- Your benefits**
- flexFit casing system: Many accessory parts and options can be fixed to the welding machine using conventional slot nuts
 - LED information bar: Indicates the current operating status
 - Energy-saving thanks to high efficiency and standby function
 - Best suited for use with long hose packages
 - Connection capability for remote control and function torch
 - Easy, tool-free change of welding polarity
 - Insulated wire space
 - IP23 spray water protected
 - Optional network connectivity with the ewm Xnet software via an integrated or external gateway
 - PC interface for PC300 XQ software
 - The high 1500 W cooling capacity, high-performance centrifugal pump and 8-litre coolant tank make for excellent torch cooling, resulting in cost savings on consumables
 - Free WPQR package for certification up to and including EXC2 in accordance with EN 1090 and for welding of unalloyed steels up to and including S355

DATA SHEET

Titan XQ 400 AC puls DW

Version	Titan XQ 400 AC puls D W R1 5m
Setting range for welding current	5 A - 400 A
Duty cycle 40 °C	400 A / 80 % 370 A / 100 %
Open circuit voltage	82 V
Mains voltage (ex works)	3 x 380 V - 400 V
Mains tolerances (ex works)	-25 % up to +20 %
Mains frequency	50 Hz / 60 Hz
Recommended generator power	23.8 kVA
Efficiency	88 %
Power consumption Pi	28 W
Cooling capacity at 1 l/min.	1500 W
Pump pressure	3.5 bar
Tank capacity	8 l
Protection classification	IP23
Test mark	CE UK ENE S
EMC class	A
Dimensions (L x B x H)	1150 mm x 678 mm x 972 mm 45.3 inch x 26.7 inch x 38.3 inch
Weight	128.5 kg / 283.3 lbs
Standards	IEC 60974-1, -2 and -10 CL.A

Configurations

Item no.	Designation
090-005607-00000	Titan XQ 400 AC puls D. Multiprocess MIG/MAG AC/DC pulse welding machine including all characteristics and welding
092-003303-00000	OW F06W. Water cooling
092-003306-00000	OW Cover. No control
092-003316-00000	OW F06R1. Wheel kit with single cylinder mount
092-003349-00000	OW MCord 6 mm ² 5m. Mains connection lead, 5 m
092-004116-00000	OW 380-400V. Mains voltage 380-400 V !-cannot be modified retrospectively-!